CON-OM. MAVERICK X3 X ds TURBO RR

HIGHLIGHTS

nightigh 15		
DEFIANT	 Trademark Can-Am DNA with next generation design Low seating position Ergo-Lok cockpit with four-way adjustable seats 	
POWERFUL	Industry-leading 195 hp turbocharged and intercooled Rotax® ACE engine Advanced airflow dynamics QRS-X transmission	
PRECISE	TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features	
PLATFORM FEATURES	• 64 in. wide • 102 in. wheelbase • 14 in. of ground clearance • High torque Dynamic Power Steering (DPS™) • 20 in. suspension travel • Rear tow hook	
SPECIFIC TO X ds TURBO RR PACKAGE	• 195 hp Turbo RR engine • Smart-Lok* front differential • FOX¹ 2.5 PODIUM¹ RC2 piggyback shocks • 14 in. aluminum beadlock wheels • 29 in. Maxxis¹ Bighorn 2.0¹ tires • X-package graphics/seats • 7.6 in. digital display with keypad • Can-Am LED signature • Painted color options	

ENGINE	TURBO RR
Туре	195 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high-airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 piggyback with dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/20 in. (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM RC2 piggyback with dual speed compression, rebound adjustments and bottom-out control
TIRES & WHEELS	
Front Tires	Maxxis Bighorn 2.0 29 x 9 x 14 in. (73.7 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 29 x 11 x 14 in. (73.7 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes



Desert Tan, Carbon Black & Can-Am Red / TURBO RR

DIMENSIONS & CAPACITIES

07 11 7 10 1 1 1 2 0	
Estimated Dry Weight	1,501 lb (680.9 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	132 x 64 x 65.7 in. (335.3 x 162.5 x 166.9 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A
Protection	Integrated front bumper Quarter-doors HMWPE full skid plate Rear tow hook
WARRANTY	
Factory Warranty	2 years BRP limited warranty



with hydraulic twin-piston calipers